



WBM Feedlot Buckets are designed specifically for handling bales and loading silage in agricultural feedlot applications.

These buckets are available in either Bale/Silage or Corral bucket configurations. Bale/Silage buckets differ by having a larger, concave (smaller) radius on the leading edge, and the basket is taller to allow for better round bale handling than the Corral bucket, creating approximately $\frac{1}{4}$ yd increase in capacity over the Corral bucket. The tips on their overarm are also designed with extended length to increase penetration and hook into bales, increasing capacity in silage loading applications.

FEATURES AND BENEFITS

- Durable construction extends wear life and stands up to rigorous application
- 4-point hook-up that is self-aligning, low maintenance and extremely strong decreases down time
- Oversized pivot bars increase strength and durability
- Extended tip aids in penetration of material to maximize carrying capability
- Overarm tips in full open position do not protrude past bucket bolt-on edges to allow for cleaning against fences, shelters, etc.
- Dual cylinders provide a positive clamping force
- Available with WLKAT or OEM pin-on lugging
- Available in a wide variety of widths and capacities

Continued on next page >>



Bale/Silage Configuration



Corral Configuration



STANDARD SPECIFICATIONS

BASKET

- 44,000 psi yield strength shell, strongbacks (frog) and sideplates
- Additional gusset plates for cylinder lugs
- 450 Brinell base edge, leading edge, weld-on heel plates, and weld-on side seam (wrap around) plates; base edge is drilled for OEM bolt-on edges

OVERARM

- Dual oversized pivot bars
- 44,000 psi yield strength tines, 2-1/2" diameter pivot pins
- Dual hydraulic cylinders
- Hydraulic crossover relief valve to protect cylinders

MACHINE SERIES	WBM MODEL #	DESCRIPTION	WEIGHT (lbs)
WL125	WL125-FLCB-2.25	2.25 cu.yd.	3,900
WL125	WL125-FLBB-2.50	2.50 cu.yd.	3,925
WL150	WL150-FLCB-2.50	2.50 cu.yd.	4,160
WL150	WL150-FLBB-2.75	2.75 cu.yd.	4,150
WL175	WL175-FLCB-3.00	3.00 cu.yd.	4,500
WL175	WL175-FLBB-3.25	3.25 cu.yd.	4,500
WL175	WL175-FLCB-3.50	3.50 cu.yd.	4,700
WL200	WL200-FLCB-3.75	3.75 cu.yd.	5,450

Includes WBM Q/C lugs and full width overarm. Base edge drilled for bolt-on edges (not included). Skidder tire option available.